



## Features

Used for lock, handle, hinge and latch slot and channel opening processes with rotating the profile on 3 surfaces of aluminum and plastic profiles.

- Copy assembly matching the process
- Ability to open various channels independently of the copy assembly with profile gauges
- Pneumatic clamps
- Triple grip slot drilling system
- · Independently operating motors
- Independent milling process on 3 different surfaces

## Standard Equipments

- Cooling system
- 8 mm milling cutter
- Profile gauge

## **Optional Equipments**

- Special copy assembly
- 5 -10 mm milling cutter



]			(×3)		dø		Z2		Z1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Z2				The second secon
HF kV		Hz	l (230 V)	øD	ø d	X1	Y1	Z1	X2	Y2	Z2	Air Pressure	Air Consumption	l x w x h (mm)
1,t 1,	rn m	200	5,6 A	8 mm	8 mm	460 mm	210 mm	210 mm	430 mm	240 mm	145 mm	6 - 8 bar	9 L / min.	2815 x 1430 x 1815 290 kg

ÖZÇELİK MAKİNA continuously improves its products and offers new and modern solutions for PVC and Aluminum Profile Processing. Accordingly, ÖZÇELİK has the right to change the information in this document without any notice. All dimensions and weights are reference values. Valid from January 2022